



SPECIFICATION	
SPEC MODEL	RMT-2302-IX
COOLING CAPACITY	31,200 kcal/h (36.26 kW) 25,600 kcal/h (29.6 kW)
VOLUME	110 CMM / 90 CMM (60/50 Hz)
BLOWER MOTOR	SIROCCO AS-111D
MOTOR	3PH/50 Hz/0.75 kW x 6 P x 2 EA
TYPE	HERMETIC SCROLL
CAPACITY	3 PH/50 Hz/3.79 kW x 2 EA
TYPE	MULTI-PASS CROSS FINNED TUBE
EVAPORATOR	-
SPEC	-
CAPACITY	12,900 kcal/h (15 kW)
TYPE	SUS-AERO FINNED TUBE TYPE
STEP	3.75 kW x 4 STEP
CAPACITY	8 L/h
TYPE	ELECTRODE
STEP	6.1 kW
HUMIDIFIER	-
TYPE	VINYL CHLORIDE + POLYESTER 20t
AIR FILTER	1025 x 415 x 2EA
FRAME SIZE	1446 x 776 x 1900
REFRIGERANT	R-22 / R407C

NO	PART NAME	DESCRIPTION	QTY	SAFETY
01	COMPRESSOR	-	2	<SAFE>
02	SERVICE VALVE	19.05 mm,15.87mm	4	<SAFE>
03	BLOWER MOTOR	SGCC	2	<SAFE>
04	BLOWER MOTOR	-	2	<SAFE>
05	EVAPORATOR	CU + AL	1	<SAFE>
06	EXPANSION VALVE	5 R/T	2	<SAFE>
07	ELECTRIC HEATER	SIS	1	<SAFE>
08	RECEIVER TANK	ST12	2	<SAFE>
09	HUMIDIFIER	-	1	<SAFE>
10	CONTROL BOX	CR SHEET 1.6t	1	<SAFE>
11	-	-	1	<SAFE>
12	L.T.C	-	2	<SAFE>
13	SENSOR	TEMP.HUMID	1	<SAFE>
14	SUCTION STRAINER	19.05 mm	2	<SAFE>
15	FILTER DRIER	12.7 mm	2	<SAFE>
16	SIGHT GLASS	12.7 mm	2	<SAFE>
17	SOLENOID VALVE(R)	12.7 mm	2	<SAFE>
18	FRAME	CR SHEET 2.3t	1	<SAFE>
19	CASE	CR SHEET 1.2t	1	<SAFE>
20	INSULATION	PU FOAM 25t	1	<SAFE>
21	DRAIN PLATE	SUS304	1	<SAFE>
22	SOLENOID VALVE(W)	6.35 mm	1	<SAFE>
23	MIDDLE VALVE(W)	6.35 mm	1	<SAFE>
24	D-HANDLE	-	1	<SAFE>
25	BASE FRAME	CR SHEET 2.3t	2	<SAFE>
26	AIR FILTER	-	2	<SAFE>
27	AIR GRILL	"AL"	1	<SAFE>
28	CONTROL MONITOR	-	1	<SAFE>
29	PUSH BUTTON	-	2	<SAFE>
30	DIGIPRESSURE SWITCH	HIGH,LOW,DIFF	2	<SAFE>
31	EMERGENCY SWITCH	-	1	<SAFE>
32	PUSH BUTTON SWITCH	-	1	<SAFE>
33	FRONT CASE	PUNCHING PLATE	1	<SAFE>

SCALE: S / N
 DATE: 2009. 01. 01
 FILE NAME: RMT-2302-IX
 DWG NO:
 DRAWING GRADE :
 GRADE 2
 REQUEST NO : 00-000
 LEGEND:

REV	DATE	DESCRIPTION	REVIEWED	CHECKED
Δ				

